

DESCRIPTION AND RATING

The 6BK7-B is a miniature twin triode designed primarily for use as a cascode amplifier at frequencies below approximately 300 megacycles. It is especially useful as the radio-frequency amplifier in very-high-frequency television tuners or as the intermediate-frequency preamplifier in ultra-high-frequency tuners. Its performance as a cascode amplifier is characterized by high gain and low noise figure. Electrically and physically, the 6BK7-B is a replacement for the 6BK7 and the 6BK7-A.

GENERAL

ELECTRICAL

Cathode—Coated Unipotential	
Heater Voltage, AC or DC	6.3 Volts
Heater Current	0.45 Amperes
Heater Warm-up Time*	11 Seconds

MECHANICAL

Mounting Position—Any
Envelope—T-6½, Glass
Base—E9-1, Small Button 9-Pin

Direct Interelectrode Capacitances†

	Section 1	Section 2
Grid to Plate: (g to p)	1.8	1.8 pf
Input: g to (h+k)	3.0	3.0 pf
Output: p to (h+k)	1.0	0.9 pf
Heater to Cathode: (h to k)	2.8	3.0 pf
Grid to Grid: (1g to 2g), maximum	0.004	pf
Plate to Plate: (1p to 2p), maximum	0.075	pf
Plate to Cathode: (p to k)	0.22	0.22 pf
Grounded-Grid Input: k to (h+g)	6.0	6.0 pf
Grounded-Grid Output: p to (h+g)	2.4	2.4 pf

MAXIMUM RATINGS


DESIGN-CENTER VALUES, EACH SECTION

Plate Voltage	300 Volts
Negative DC Grid Voltage	50 Volts
Plate Dissipation	2.7 Watts

Heater-Cathode Voltage

Heater Positive with Respect to Cathode	
DC Component	100 Volts
Total DC and Peak	200 Volts
Heater Negative with Respect to Cathode	
Total DC and Peak	200§ Volts

PHYSICAL DIMENSIONS




EIA 6-2

EIA 6-2

TERMINAL CONNECTIONS

- Pin 1—Plate (Section 2)
- Pin 2—Grid (Section 2)
- Pin 3—Cathode (Section 2)
- Pin 4—Heater
- Pin 5—Heater
- Pin 6—Plate (Section 1)
- Pin 7—Grid (Section 1)
- Pin 8—Cathode (Section 1)
- Pin 9—Internal Shield‡

BASING DIAGRAM



EIA 9AJ

CHARACTERISTICS AND TYPICAL OPERATION

CLASS A₁ AMPLIFIER, EACH SECTION

Plate Voltage.....	150	Volts
Cathode-Bias Resistor.....	56	Ohms
Amplification Factor.....	43	
Plate Resistance, approximate.....	4600	Ohms
Transconductance.....	9300	Micromhos

* The time required for the voltage across the heater to reach 80 percent of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the rated heater voltage divided by the rated heater current.

† Without external shield.

‡ It is recommended that pin 9 be grounded.

Plate Current.....	18	Milliamperes
Grid Voltage, approximate		
I _b = 10 Microamperes.....	-11	Volts
Noise Figure π	7	Decibels

§ When the tube is used as a cascode amplifier and the two sections are connected in series, this voltage may be as high as 300 volts maximum under cutoff conditions.

π As measured in a cascode amplifier which has a balanced 300-ohm input system and which operates at a plate supply voltage of 250 volts, a plate current of 18 milliamperes, a frequency of 200 megacycles, a stage bandwidth of 7 megacycles, and an effective noise bandwidth of 3.5 megacycles.

Design-Center ratings are limiting values of operating and environmental conditions applicable to a bogey electron tube of a specified type as defined by its published data and should not be exceeded under normal conditions.

The tube manufacturer chooses these values to provide acceptable serviceability of the tube in average applications, making allowance for normal changes in operating conditions due to rated supply-voltage variation, equipment

component variation, equipment control adjustment, load variation, signal variation, environmental conditions, and variations in the characteristics of the tube under consideration and of all other electron devices in the equipment.


The equipment manufacturer should design so that initially no design-center value for the intended service is exceeded with a bogey tube under normal operating conditions at the stated normal supply voltage.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or

elements. In the absence of an express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.


AVERAGE PLATE CHARACTERISTICS

EACH SECTION




AVERAGE TRANSFER CHARACTERISTICS


EACH SECTION



AVERAGE CHARACTERISTICS




AVERAGE PLATE CHARACTERISTICS



AVERAGE TRANSFER CHARACTERISTICS

CASCODE CONNECTION



AVERAGE TRANSFER CHARACTERISTICS

CASCODE CONNECTION

